


MICROMIKKO



Il proiettore Micromikko offre soluzioni architettoniche molteplici a lighting designers ed architetti. Design essenziale, ricchezza di accessori ed elevate performances ottiche ne completano le caratteristiche. L'ampia gamma di soluzioni LED disponibili risponde alle esigenze di risparmio energetico e riduzione dei costi di manutenzione.

Micromikko floodlight offers a variety of architectural solutions to both lighting designers and architects. Main distinguish characteristics are pure design, wide range of accessories and high value optic systems. The range of powerful LEDs available meets different goals, both in terms of energy savings and cost reduction for maintenance.






5966.CAS.T.-- 9W LED 3000K 1170lm
19° ^

220-240V 50/60hz 
alimentatore incluso *LED driver integral*

5966.CAM.T.-- 9W LED 3000K 1170lm
40° ^

220-240V 50/60hz 
alimentatore incluso *LED driver integral*

-  **.05** grigio antracite
anthracite grey
-  **.13** grigio chiaro
light grey

ACCESSORI ACCESSORIES


 **206-IP67**
Alimentatore 500mA SELV
1 per 1Micromikko 9W
LED driver 500mA SELV
1 for 1Micromikko 9W

 **204**
Connettore rapido IP68
IP 68 fast connector

 **224**
Visiera in alluminio
aluminium hood

 **642**
Cintura di sostegno
Support belt

 **257**
Picchetto
Stake




5974.CAS.T.-- 9W LED 3000K 1170lm
19° ^

220-240V 50/60hz 
alimentatore incluso *LED driver integral*

5974.CAM.T.-- 9W LED 3000K 1170lm
40° ^

220-240V 50/60hz 
alimentatore incluso *LED driver integral*



5984.CAS.T.-- 9W LED 3000 K 1170lm
19° ^

max 500mA DC 
alimentatore remoto SELV non incluso
remote SELV LED driver not included

5984.CAM.T.-- 9W LED 3000 K 1170lm
40° ^

max 500mA DC 
alimentatore remoto SELV non incluso
remote SELV LED driver not included