

# PRAGMA T

design Francesco Brivio




Elegante lampada dalla luce diffusa. Il paralume in policarbonato opalino o cotone plissettato, impreziosito dalla struttura in alluminio, rende la luce emessa da questo apparecchio morbida ma al contempo netta, delicata ma decisa. Pragma è disponibile sia nella versione a sospensione, da terra e tavolo. divenendo in ogni sua conformazione un elemento di design per l'ambiente circostante.

*Elegant light providing diffused lighting with an opal diffuser of polycarbonate or pleated cotton. Structure in die-cast aluminium and steel suspension cable. It is possible to mount the lamp off centre by use of a decentralizing support. Available in suspension, floor lamp and table versions.*



# PRAGMA T




**02315.--**  
340°  $\wedge$   
220-240V 50/60hz

E27 max 105W

Colore standard 1 settimana  
Standard color 1 week

- **.19** Grigio argento  
Silver grey (matt)
- **.50** Cromo lucido  
Polished chrome



**01212.--**  
340°  $\wedge$   
220-240V 50/60hz

E27 max 105W

# LINEAR



Lampada dal design essenziale e lineare, la sua installazione può avvenire ad incasso o a muro con emissione di luce diretta. La regolarità e la semplicità del corpo illuminante consentono di inserire questo apparecchio in diverse ambientazioni: singola in contesti residenziali, o modulare in ambienti contract o centri direzionali. Il comfort visivo generato da questo apparecchio è garantito dalla presenza del diffusore opalino che chiude il corpo della lampada, emettendo una luce morbida ma dalle elevate prestazioni.


*Recessed or wall mounted fixture with essential linear design covers a wide range of installations. Its simple design allows various installations including residential spaces, contract environments and executive headquarters. Available as single mount or with a modular system. Opal diffuser delivers soft high quality light.*



Colore standard 1 settimana  
Standard color 1 week

● .48 Alluminio naturale  
Smatt white aluminium


# LINEAR



**20832.--.31** 7W LED 3000K 600lm  
110° ^  
500 mm  
24V 50/60hz  
alimentatore remoto SELV non incluso  
*remote SELV LED driver not included*

**20833.--.31** 14W LED 3000K 1200lm  
110° ^  
1000 mm  
24V 50/60hz  
alimentatore remoto SELV non incluso  
*remote SELV LED driver not included*


**20834.--.31** 28W LED 3000K 2400lm  
110° ^  
2000 mm  
24V 50/60hz  
alimentatore remoto SELV non incluso  
*remote SELV LED driver not included*



**20820.--.31** 7W LED 3000K 600lm  
110° ^  
500 mm  
24V 50/60hz  
alimentatore remoto SELV non incluso  
*remote SELV LED driver not included*

**20821.--.31** 14W LED 3000K 1200lm  
110° ^  
1000 mm  
24V 50/60hz  
alimentatore remoto SELV non incluso  
*remote SELV LED driver not included*


**20822.--.31** 28W LED 3000K 2400lm  
110° ^  
2000 mm  
24V 50/60hz  
alimentatore remoto SELV non incluso  
*remote SELV LED driver not included*



**20829.--.31** 7W LED 3000K 600lm  
110° ^  
500 mm  
24V 50/60hz  
alimentatore remoto SELV non incluso  
*remote SELV LED driver not included*

**20830.--.31** 14W LED 3000K 1200lm  
110° ^  
1000 mm  
24V 50/60hz  
alimentatore remoto SELV non incluso  
*remote SELV LED driver not included*

**20831.--.31** 28W LED 3000K 2400lm  
110° ^  
2000 mm  
24V 50/60hz  
alimentatore remoto SELV non incluso  
*remote SELV LED driver not included*



**20801.--.31** 7W LED 3000K 600lm  
110° ^  
500 mm  
24V 50/60hz  
alimentatore remoto SELV non incluso  
*remote SELV LED driver not included*

**20802.--.31** 14W LED 3000K 1200lm  
110° ^  
1000 mm  
24V 50/60hz  
alimentatore remoto SELV non incluso  
*remote SELV LED driver not included*

**20803.--.31** 28W LED 3000K 2400lm  
110° ^  
2000 mm  
24V 50/60hz  
alimentatore remoto SELV non incluso  
*remote SELV LED driver not included*

## ACCESSORI ACCESSORIES



**20885**  
Clip fissaggio acciaio  
*Steel fixing clip*



**22028**  
Alimentatore SELV IP40 50W 24V DC 0-3 metri  
*LED driver SELV IP40 32W 24V DC 0-3 meters*



**20886**  
Clip fissaggio plastica  
*Plastic fixing clip*

**22029**  
Alimentatore SELV IP40 100W 24V DC 0-6 metri  
*LED driver SELV IP40 100W 24V DC 0-6 meters*

progetto grafico

*graphic layout*

studio Ghidini

impaginazione

*graphic designer*

studio Ghidini

Coordinamento e supervisione

*supervising*

studio Ghidini

stampato nel mese di Agosto 2018

*printed in August 2018*

I dati presenti in questo catalogo sono forniti a titolo indicativo. Ghidini Lighting srl si riserva il diritto di variarli in qualsiasi momento e senza preavviso. Consultare il sito web per i dati aggiornati.

*The data presented in this catalogue are purely indicative. Ghidini Lighting reserves the right, at its sole discretion, to change, modify, add or remove portions of these data, at any time. Refer to the website for updated information.*

I dati fotometrici presenti nel catalogo si riferiscono al flusso della sorgente; consultate i file tecnici fotometrici del sito web per il flusso nominale degli apparecchi.

*The photometric data provided on this catalogue are referred to the light source; the photometric data of the luminaire it can be checked on the technical photometric file on the website.*

**Ghidini Lighting s.r.l.**  
Via Monsuello, 211 25065  
Lumezzane (Brescia) Italy  
[www.ghidini.it](http://www.ghidini.it)  
[www.lucitalia.it](http://www.lucitalia.it)

OUTDOOR & INDOOR HOME LIGHTING

 GHIDINI LUCITALIA