


STELO C



STELO 0


STELO 1

Lampada a soffitto dal design essenziale a luce diretta. Regolarità e semplicità sono le parole chiave di questo apparecchio. La purezza incontaminata del corpo illuminante si presta perfettamente a creare delle composizioni con questa lampada, grazie alle diverse lunghezze e dimensioni in cui essa è disponibile. Le molteplici finiture materiche disponibili lo rendono inoltre versatile in diversi contesti; Stelo diventa infatti un elemento dal design raffinato per sale da pranzo, spazi commerciali, o luoghi d'accoglienza. Per una maggiore versatilità l'apparecchio dispone inoltre di due tipologie di ottiche: concentrante o diffusa, garantendo la perfetta illuminazione degli ambienti in cui viene inserito.


Ceiling luminaire with essential design and direct light emission. Its simple design allows for various installations including residential spaces, contract environments and executive headquarters. The uncontaminated purity of the design lends perfectly to creating compositions with multiple lamps, thanks to the various lengths and sizes it is available in. Concentrated or diffused optics available, furthering its versatility.



Finiture speciali
Special finishes




23102.--.31 6W LED 3000 K 800lm
30° ^
220-240V 50/60hz
alimentatore incluso *LED driver integral*



23104.--.31 6W LED 3000K 800lm
30° ^
220-240V 50/60hz
alimentatore incluso *LED driver integral*

Colore standard 1 settimana
Standard color 1 week

 **.01** Bianco
White (matt)

Colore su richiesta 2 settimane
Upon request color 2 weeks


 **.19** Grigio argento
Silver grey (matt)

 **.22** Nero
Black (matt)

 **.45** Ruggine
Rust

Colore su richiesta 4/6 settimane
Upon request color 4/6 weeks

 **.27** Nero - oro
Black - gold


 **.25** Bianco - oro
White - gold

 **.72** Nero - rosso
Black - red

 **.71** Bianco - rosso
White - red



23111.--.31 12W LED 3000K 1800lm
30° ^
220-240V 50/60hz
alimentatore incluso *LED driver integral*



23112.--.31 12W LED 3000K 1800lm
30° ^
220-240V 50/60hz
alimentatore incluso *LED driver integral*